

Practical AI for Autonomous Robots

Day 1: Introduction to Robotic Software and Architectures

Dr. Timothy Wiley

School of Computing Technologies
RMIT University



ESSAI July 2025





Acknowledgement of Country

RMIT University acknowledges the people of the Woi wurrung and Boon wurrung language groups of the eastern Kulin Nation on whose unceded lands we conduct the business of the University.

RMIT University respectfully acknowledges their Ancestors and Elders, past and present.

RMIT also acknowledges the Traditional Custodians and their Ancestors of the lands and waters across Australia where we conduct our business.

Artwork 'Luwaytini' by Mark Cleaver, Palawa



About me: Dr. Timothy Wile

PhD, Online Learning of Robotic Behaviours,
UNSW Australia

Lecturer, Artificial Intelligence,
School of Computing Technologies
STEM College, RMIT University

Manager,
Artificial Intelligence Innovation Lab

Research Interests:

- Autonomous Robotics
- Reinforcement Learning
- Qualitative Reasoning
- Uncrewed Ariel Systems
- Sim2Real



Robot Soccer



What is Autonomous Robotics?

—
ESSAI July 2025




What defines an Autonomous Robot?

What defines an autonomous robot to you?





— Shakey the Robot



Nilsson, N. J. (1982). Principles of Artificial Intelligence. Berlin Heidelberg: Springer-Verlag





What defines an Autonomous Robot?

Aside from the obvious “act autonomously” that is, “think-and-act for themselves”:


- Perceive the environment
- Interact with the environment
- Internal reasoning

What separates robotics from other fields of AI is the physical input/output





RoboCup Soccer – Aibo





— RoboCup Soccer – Aibo





RoboCup Soccer – Nao





RoboCup Soccer – Nao





--- DARPA Rescue Challenge



DeepMind Learning Soccer





Boston Dynamics ATLAS motion



About the Course

—
ESSAI July 2025





This Course is about...

- Overview of Autonomous Robotics
- Give a breadth of knowledge rather than a depth
- Provide operational knowledge on autonomous robotic system for later in-depth study
- Applied AI/ML
- Hopefully convince you to work in robotics 😊





— This course presumes...

- Some familiarity with common AI techniques such as:
 - Graph algorithms
 - Heuristic Search (A^*)
 - Random Sampling
 - Reinforcement Learning fundamentals
 - Machine Learning fundamentals
 - Neural Network structures





Topics

Day 1: Introduction to Robot System + Learning Robot Control

Day 2: Motion Planning and Navigation

Day 3: Localisation and Mapping

Day 4: Robotic Vision

Day 5: Symbolic Task Planning and Planning with LLMs



Motivating Example

—
ESSAI July 2025





— Problem: Maze






Problem: Maze





Solution: With AR Visualisation & Control





—
Solution: To touch each marker



Elements of Robots

—
ESSAI July 2025






— ROSbot






Panther






Nao V6





— Shakey the Robot

Shakey the Robot: The First Robot to Embody Artificial Intelligence




Autonomous Agent Model

—
ESSAI July 2025




AI Agent Models



Russel & Norvik. *Artificial Intelligence: A Modern Approach* (2017),




AI Agent Models



Russel & Norvik. *Artificial Intelligence: A Modern Approach* (2017),




AI Agent Models



Russel & Norvik. *Artificial Intelligence: A Modern Approach* (2017),



AI Agent Models




Autonomous Software Components


—
ESSAI July 2025



Autonomous Robot Software Components



ROSBot Maze



RoboCup Soccer

World Modelling

- Localisation
- Ball / Robot persistence
- Team Coordination & Shared State
- Moving object trajectory prediction

Navigation

- Path Planning
- Dynamic obstacle avoidance
- Prediction of kicks

Soccer Skills

Sensor Processing

- Ball Detection
- Field Feature Detection
- Robot Detection

Control

- Bi-pedal Walk & Balance
- Head & Arm Control
- Kicks
- Get-ups



Software Architectures

—
ESSAI July 2025




Software Architectures: Sense-Plan-Act



Nilsson, N. J. (1982). Principles of Artificial Intelligence. Berlin Heidelberg: Springer-Verlag




Software Architectures: Subsumption



R. A. Brooks (1986), "A Robust Layer Control System for a Mobile Robot", IEEE Journal of Robotics and Automation RA-2, 14-23




Software Architectures: Three-Layer



Bonasso, P. et. al. (1997). Experiences with an architecture for intelligent, reactive agents. Journal of Experimental & Theoretical Artificial Intelligence 9(2-3):237– 256



Software Architectures: RCS



Albus, J. S. & Barbera, A. J. (2005) RCS: A cognitive architecture for intelligent multi-agent systems. *Annual Rev Control* 29, 87–99.



World Modelling

- Localisation
- Mapping

Navigation

- Path Planning
- Execution and Search
- Obstacle Avoidance

Behaviour Decision Making Planning

Sensor Processing

- Vision
- Audio

Control

- Locomotion
- Grasping
- Motion Planning



DeepMind Learning Soccer



Learning Motion

A practical perspective for
Reinforcement Learning

—
ESSAI July 2025



Day Dreamer





Learning Motion

Algorithms for robot motion must handle a variety of issues unique to the realities of real-world control, including:

- Noise
- Slip
- Hardware failures
- Probabilistic Actions
- Non-deterministic Actions

Reinforcement Learning is a very popular approach as various RL forms can help account for these issues without ‘manual’ intervention.

We could devote a whole course to this topic. For today we’ll keep this to a high-level of how RL methods are applied for robot control, and leave a deep-dive for your own investigations.




Reinforcement Learning – Overview

An RL problem can be minimally defined as:

$$RL := \langle S, A, T, V, R, \gamma, \pi \rangle$$

Where:

- S – State Space (discretised, continuous)
- A – Action Set (discrete, continuous)
- T – Transition Function (model-based, or model-free)
- V – Value Function
- R – Reward Function
- γ – Discount Factor
- π – Policy Function






Markov Decision Process

An RL problem defines a Markov Decision Process (MDP) where:

- The decision of which action to perform in a state only requires information that is available in the current state
- The history of states and decisions that the agent took in reaching its current state has no impact on the decision

It is critical that a RL problem is properly defined as an MDP.





Value, Policy, and Q Functions

1. Value function: $V: S \rightarrow \mathbb{R}$

$$V(s) = E[r_i + r_{i+1} + \dots + r_{i+t}] = E\left[r_i \sum_{j=1}^t + r_{i+j}\right]$$
$$V(s) = (1 - \alpha)V(s) + \alpha \max_a [R(s, a) + \gamma V(T(s, a))]$$

2. Policy function: $\pi: S \rightarrow A$

$$\pi^*(s) = \operatorname{argmax}_a [R(s, a) + \gamma V(T(s, a))]$$

3. Q-Learning: $Q(S \times A) \rightarrow A$

$$Q(s, a) = (1 - \alpha)Q(s, a) + \alpha [R(s, a) + \gamma \max_{a'} Q(s', a')]$$





Learning Motion

All variates of RL forms can be used within a robotics context:

- On policy learning
 - SARS, Value/Policy iteration
- Off-policy learning
 - Classic Q-learning
- Model-free methods
 - Deep Q-Learning
 - Actor-Critic
 - PPO
- Model-based
 - Dreamer / Day Dreamer

... to name a few





Learning Motion: Issues

Reinforcement Learning methods encounter issues:

- Iterations required for convergence
- Balancing Exploration vs Exploitation
- Appropriate definition of the RL problem
- Transferring simulated behaviours to real-systems

This field is rapidly changing.



Classic Example – Cart and Pole

For simplified domains, a traditional representation with any combination of value iteration, policy iteration, q-learning, etc., are successful:


$$RL := \langle S, A, T, V, R, \gamma, \pi \rangle$$

S – Cart/pole position

A – L/R force

T – Either model-based or model-free

R – Balancing time, distance from centre, etc.



Learning Motion: Examples





Deep Reinforcement Learning

Deep Reinforcement Learning methods use the non-linear piecewise function representative power of deep neural networks to encode various parts of the RL problem definition, replacing them with Deep networks.

One of the first successful forms of DRL (2013), is the Deep Q-Network (DQN). Google DeepMind trained a

Model-Free methods: DQN, PPO, SAC, TD3

Model-Based methods: Plan2Explore, Dreamer, Day Dreamer

Mnih, Volodymyr, et al. "Playing atari with deep reinforcement learning." arXiv preprint arXiv:1312.5602 (2013).




DQN (Deep Q-Network)

$$RL := \langle S, A, T, V, R, \gamma, \pi \rangle$$

This essentially represents the Q-learning Q-function $Q(s, a)$ as a Deep Network. In DQN, the Q-function gives the Loss Function:

$$L(\theta) = E[y - Q(s, a, \theta)^2]$$






Actor-Critic RL

$$RL := \langle S, A, T, V, R, \gamma, \pi \rangle$$

Actor-Critic RL, such as TD3 and SAC, has two components:

- **Actor:** decides which action to take in a state, represented by a DNN that outputs action probabilities or deterministic actions
- **Critic:** evaluates the quality of the actions taken by the actor, estimating the value of states or actions (ie. the value function)

This essentially models classic RL, where the value and policy functions are independently computed. The error from the critic updates the actor.





--- DRL – PPO

PPO (2017) is an extension to SAC and DQN that address the problem of instability in the value/policy networks as well as improving the capability of learning. PPO has now become the standard method for DRL.

PPO introduced concepts of:

- The Advantage
- Clipping
- An Objective Function (to replace the Q- function)

Schulman, John; et. a. (2017), Proximal Policy Optimization Algorithms, arXiv:1707.06347





DRL – PPO

The PPO loss-function is

$$L(\theta) = \mathbb{E}_t[\min(r_t(\theta)A_t, \text{clip}(r_t(\theta), 1 - \epsilon, 1 + \epsilon)A_t))]$$

This finds the expectation of the best advantage at each timestep t

- r_t is the ratio of the probability of selecting an action under the old or new policies, and is not to be confused with the reward!
- A_t is the advantage of an action at timestep t
- ϵ is a hyper-parameter controlling how much each update is clipped






DRL – Dreamer/DayDreamer

As model-free methods don't have an explicit transition function, the the value and policy functions must also “internally encode” approximations of the transitions.

Model-based methods provide an explicit model, which can improve learning. DayDreamer (2023*) is one of the state-of-the-art methods with two deep networks:

- Latent world model models environment dynamics to predict future observations, rewards, and values in latent space.
- Behaviour model - Actor-Critic RL that incorporates world model state predictions

Wu, P., Escontrela, A., Hafner, D., Goldberg, K. & Abbeel, P. DayDreamer: World Models for Physical Robot Learning. in Conference on robot learning 2226–2240 (PMLR, 2023)



Noon Gudgin

Thank you

Day 2:
Motion Planning and
Navigation

ESSAI July 2025

